





VERSATILITY & RELIABILITY

Payload. Total Vehicle Capacity of up to 567 kg (1250 lb).

Street legal. Carryall LSVs can be driven on public streets in several countries. Check your country-specific laws.

Green. Reduce your carbon footprint and cut fuel costs with this sturdy electric vehicle.

Safety-equipped. Carryall LSVs come with all required safety equipment: headlights, tail lights, turn signals, 3-point safety belts, hip restraints and more.

Improved charging. The industry's only standard on-board high-efficiency charger with cord retractor. This new system operates on voltages around the globe, and tolerates voltage swings that would shut down lesser chargers.

More durable than steel. Carryalls are built on Club Car's exclusive lightweight, rustproof, air-craft-grade aluminum frame that's designed to be stronger than steel. Unlike competitive steel frames, it resists corrosion and retains resale value.

Fit-to-task utility. A one-of-a-kind bed box with an integrated track-based attachment system, optional tool holders, bed dividers and cargo tie downs increases versatility and saves floor space. So you can do more with less.

The best warranty in the industry. The industries longest standard battery, powertrain and bumper to bumper warranty.

CATEGORY	510 ELECTRIC	710 ELECTRIC
Vehicle	Homologation 2002/24/EC (Cat L7e) Quadricycle Directive	
Engine/Motor Type	48V 3-phase AC	
Controller	400 Amp - Solid State	
Horsepower (Rated)	3.3 kW (4.4 hp), Peak 11.7 kW (16 hp)	
Transmission	Direct drive, double reduction helical gear	
Gear Selection	Forward/Neutral/Reverse	
Gear Ratio	12.32:2	
Battery	Eight 6V Flooded Lead Acid	
Charger	DeltaQ QuiQ (1 kW High Frequency)	
Lighting	37.5 Watt Halogen headlights, turn signals, horn, and LED taillights/brake light	
Steering Mechanism	Self-adjusting Rack and Pinion	
Suspension (Front)	Independent leaf spring with dual hydraulic shocks	
Suspension (Rear)	Independent leaf spring with dual hydraulic shocks	
Brakes	4-wheel hydraulic disk/drum	
Park Brake	Hand Operated, Multi-lock	
Body (Front & Finish)	ArmorFlex with automotive paint/clearcoat	
Body (Rear)	Aluminum	
Tires (Front)	205-65-10 6-Ply, E-mark	
Tires (Rear)	205-65-10 6-Ply, E-mark	
Wheelbase	198.3 cm (78.1 in)	251.7 cm (99.1 in)
Overall Height	188.72 cm (74.3 in)	
Overall Length	299.7cm (118 in)	349.3 cm (137.5 in)
Bed L x W x H (Cargo Box)	117.6 x 126.5 x 26.7 cm (46.3 x 49.8 x 10.5 in)	171.7 x 126.5 x 26.7 cm (67.6 x 49.8 x 10.5 in)
Ground Clearance (Differential)	14.2 cm (5.6 in)	
Track Width (Front)	87.8 cm (34.6 in)	
Track Width (Rear)	99.5 cm (39.2 in)	
Max Width (w/o Mirrors)	127.7 cm (50.3 in)	
Total Vehicle Capacity	430.0 kg (950 lb)	567.0 kg (1250 lb)
Bed Load Capacity	249.5 kg (550 lb)	385.6 kg (850 lb)
Towing Capacity	567.0 kg (1250 lb)	
Combined Gross Vehicle Capacity	567.0 kg (1250 lb)	
Tongue Weight	68.0 kg (150 lb)	
Max Speed	40 kph (25 mph)	
Warranty	2 year/2000 hour limited warranty	

ACCESSORIES & OPTIONS

- 1. Wheel Cover
- 2. Brush Guard
- 3. Flatbed
- 4. Stakeside
- 5. Cargo Box
- 6. Rear Receiver Hitch
- 7. Cab (Shown with optional glass doors)
- 8. Vehicle Colors



