

Options and Accessories



Lighting Package*



Turn Signals



One-Piece Windshield



Fold-Down Windshield



West Coast Mirror/Heavy-Duty Bumper



Glove Box With Lock



Fold-Down Seat



Heavy-Duty Batteries



Hour Meter



Extra-Traction Tires



Communication Display Module



Wheel Covers



Canopy Top White and Beige



5-Panel Mirror



3-Sided Enclosure

*Headlights, Taillights, Brakelights and Horn

Club Car supports only the safe and legal use of our products. To reduce the risk of injury, always operate and travel within these vehicles in a safe, lawful and conscientious manner. The vehicles referenced herein are designed and manufactured for off-road use only. As such, they do not conform to Federal Motor Vehicle Safety Standards for automobiles or Low Speed on-road motor Vehicles. For further information on these products (including a full description of the Limited Warranty), please review the applicable owner's manual or contact Club Car, Inc.

Club Car

Villager 8

TRANSPORTATION VEHICLE



Ingersoll Rand is a global diversified firm providing products, services and solutions to enhance the quality and comfort of air in homes and buildings, transport and protect food and perishables, secure homes and commercial properties, and increase industrial productivity and efficiency. Driven by a 100-year-old tradition of technological innovation, we enable our customers to create progress and a positive impact in their world.

1.800.CLUBCAR • +1 706.863.3000

www.clubcar.com www.ingersollrand.com



Villager 8

Need more room? How about room for eight? The Villager 8 seats seven passengers and a driver for your high-volume transportation business. Shuttle several people with ease and give tours more efficiently with the ability to carry more people at one time in



Club Car comfort and style. With a powerful 48-volt electric motor or 11.5 hp gas engine, the Villager 8 offers versatility for any environment.



Features

Club Car's exclusive IQ Plus System™ electric or 11.5 hp gas engine



Fixed rear seat (fold-down seat available)



Rugged, rustproof aluminum frame, and chassis



Molded, seamless vinyl seats



Self-adjusting, maintenance-free rack & pinion steering




ArmorFlex® fade-resistant front body



Standard Color: White



Optional Colors: Beige, Gray, Dark Gray, Green, Classic Blue, Red, Black and Burgundy



6-ply, premium tread tires



Smooth, independent front and semi-independent rear suspension

Additional Features

- Maximum speed of 17 mph (27.3 kph) (Electric vehicles only)
- 1,500 lb (681 kg) total vehicle capacity
- Seating for 8

- Maximum hp @ 3,600 rpm exceeds SAE J1940 Performance Standards
- Headlights, taillights, brakelights and horn

- 48-volt IQ Plus electric motor or 351 cc, 11.5 hp gas, pedal-start engine
- Four-wheel brakes
- Ergonomic dash mount shifter

Specifications

Villager 8 Electric
with exclusive IQ Plus System



Villager 8 Gasoline

POWER SUPPLY	Engine	N/A	Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
	Drive Motor	48-volt, shunt-wound	N/A
	Horsepower	3.7 hp @ 4,097 rpm (continuous) 21 hp @ 1,663 rpm (intermittent)	11.5**
	Governor	N/A	Automatic ground speed sensing, Internally geared-in unitized transaxle
	Governed RPM	N/A	3,050 +/- 30
	Ignition	N/A	Electronic w/electronic rpm limiter
	Drive Unit	12.3:1 direct-drive axle, double reduction helical gear	Unitized Transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
	Electrical System	48-volt	12-volt, 500 CCA 105 min. reserve
	Batteries	Eight 6-volt, Standard: T105 = 115 min @ 75 amps; Heavy Duty: T145 = 145 min @ 75 amps	N/A
STEERING/ SUSPENSION	Charger	Automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed; International CE marked available	N/A
	Controller	500 amp Solid State	N/A
	Steering	Self-adjusting rack & pinion	Self-adjusting rack & pinion
	Front Suspension	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
	Rear Suspension	Leaf springs with dual hydraulic shocks	Leaf springs with dual hydraulic shocks
	Brakes	Four-wheel, mechanical drum	Four-wheel, mechanical drum
FRAME/CHASSIS	Park Brake	Foot-operated, multi-lock	Foot-operated, multi-lock
	Stabilizer Bar	No	Yes
	Frame/Chassis	Aluminum I-Beam	Aluminum I-Beam
	Front Body	ArmorFlex®	ArmorFlex®
	Rear Body	ArmorFlex®	ArmorFlex®
	Body Finish	Matching paint over molded in color	Matching paint over molded in color
	Light Package	Std. Light Package	Std. Light Package
	Front Tires	18 x 6.50-8, 6-ply rated, Premium tread	18 x 6.50-8, 6-ply rated, Premium tread
DIMENSIONS	Rear Tires	18 x 6.50-8, 6-ply rated, Premium tread	18 x 6.50-8, 6-ply rated, Premium tread
	Instrumentation	Battery capacity indicator, battery warning light	Electronic fuel gauge/hour meter, low-oil warning light
	Total Vehicle Capacity	1,500 lb (681 kg)	1,500 lb (681 kg)
	Overall Length	157" (398.8 cm)	157" (398.8 cm)
	Overall Width	47.3" (120.1 cm)	47.3" (120.1 cm)
	Overall Height	48" (121.9 cm)	48" (121.9 cm)
	Wheelbase	131.5" (334 cm)	131.5" (334 cm)
	Ground Clearance Under Differential	4.5" (11.4 cm)	4.5" (11.4 cm)
	Fuel Tank Capacity	N/A	7 gallons (26.5 liters)
	Tread	34.5"/38.5" (87.6 cm/97.8 cm)	34.5"/38.5" (87.6 cm/97.8 cm)
	Dry Weight Less Batteries	704 lb (319.6 kg)	866 lb (393.2 kg)
	Speed Range	5 - 17 mph (8-27.3 kph)	14 - 16 mph (22.5-25.7 kph)
	Outside Clearance Circle	32.6 ft (9.9 m) dia.	32.6 ft (9.9 m) dia.
	Turning Radius	15.9 ft (4.8 m)	15.9 ft (4.8 m)
	Intersecting Aisle Radius	108" (274.3 cm)	108" (274.3 cm)
	Vehicle Warranty	2-year, limited/4-year batteries*	2-year, limited

*4-year, limited battery warranty for electric vehicles **Maximum hp @3,600 rpm exceeds SAE J1940 Performance Standards